Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.   (Currently amended) An image signal transmitting/receiving method comprising:

transmitting/receiving a main image signal;

checking determining whether a cut-off mode has been set for the main a main image signal; and

transmitting and displaying, during a telephonic communication, a sub-image signal instead of the main image signal in case that the cut-off mode is set set;

transmitting and displaying, during a telephonic communication, the main image signal instead of the sub-image signal in case that the cut-off mode is not set,

wherein the sub-image signal comprises one of a signal inputted by a user or a previously transmitted main image signal and is stored in a predetermined storing area.

2.   (Currently amended) The method of claim 1, wherein the main image signal is a signal to be transmitted or a received image signal.

2

3. – 6. (Canceled)

7.   (Currently amended)   An image signal transmitting/receiving apparatus comprising:

an image signal processor for processing a main image signal;

a display unit for displaying the received main image signal;

a controller for checking whether a cut-off mode has been set for the main image signal; and

an image signal selector for selectively outputting, during a telephonic communication, a sub-image signal instead of the main image signal to the image signal processor or the display unit in case that the cut-off mode has been set or outputting the main image signal to the image signal processor in case that the cut-off mode has not been set,

wherein the sub-image signal comprises one of a signal stored by a user or a previously transmitted main image signal.

8. – 9. (Canceled)

10.   (Currently amended) An image signal transmitting apparatus comprising:

an image signal processor for processing a main image signal;

a controller for checking whether a cut-off mode has been set for the main image

signal; and

an image signal selector for outputting <u>during a telephonic communication</u> a sub-

image signal instead of the main image signal to the image signal processor in case that the cut-

off mode has been set, ~~the image signal selector outputting the sub-image signal during a~~

~~telephonic communication~~<u>or outputting the main image signal to the image signal processor in</u>

<u>case that the cut-off mode has not been set,</u>

<u>wherein the sub-image signal is a signal stored by a user or the main image signal</u>

<u>that has been previously transmitted</u>.

11. – 12. (Canceled)

13.   (Currently amended) An image signal receiving apparatus comprising:

an image signal processor for processing a main image signal;

a display unit for displaying the received main image signal;

a controller for checking whether a cut-off mode has been set for the main image

signal; and

an image signal selector for outputting <u>during a telephonic communication</u> ~~an~~<u>a</u>

sub-image signal instead of the received main image signal to the display unit in case that the cut-

off mode has been set, <u>or outputting the received main image signal to the image signal display</u>

unit in case that the cut-off mode has not been set~~the image signal selector outputting the sub-image signal during a telephonic communication~~

wherein the sub-image signal comprises one of a signal stored by a user or a previously transmitted main image signal.

14. - 15. (Canceled)

16. (Previously Presented) The method of claim 1, further comprising setting the cut-off mode.

17. (Previously Presented) The method of claim 16, wherein the cut-off mode is set during telephonic communication.

18. (Previously Presented) The apparatus of claim 7, further comprising a device for setting the cut-off mode.

19. (Previously Presented) The apparatus of claim 18, wherein the cut-off mode is set during telephonic communication.

20.   (Previously Presented) The apparatus of claim 10, further comprising a device for setting the cut-off mode.